



TURNING TO
BLAND TO GRAND

Technical Data Sheet

ClearGrip™

Glass Removable Clear Self Adhesive Print Media

Carrier			
Film Type	Clear Calendered Satin Matte PVC		
Thickness (mil)	3.2		
Gloss (60° Gardner)	26 ± 6%		
Adhesive			
Adhesive Type	Specialty Glass Removable Pressure Sensitive Adhesive		
pH-value	Neutral, Approx. 7		
Weight (g/m2)	14 ± 2		
Adhesive Strength (N/25 mm)	20 min:>0.50	24h:> 1.00	PSTC 101A
Release Liner			
Type	Siliconized Embossed PP Film		
Nominal Thickness (mil)	4.0		
Weight (g/m2)	90		
Other			
Handling/Storage Conditions	18° to 25°C / 60° to 80°F; 40 to 65% relative humidity		

Advantages / Special Features

- Unique gudy® window adhesive is both removable and repositionable
- Easy apply textured adhesive allows bubble free, on site application by hand
- Premium print durability for short term, <6 month, indoor glass applications

Printability	
Latex	◆
UV	◆

Process & Handling

- Drying times vary based on ink type and ambient conditions
- Ensure inks are fully dried/cured (24 hours, in some cases) before application
- Prior to application, clean and dry the window, avoiding ammonia based cleaners
- Adhesive is formulated for indoor window glass applications



For Technical Support with any of our inkjet print materials, please call Seal Media Support at 800-257-7325, ext 8945.

October 2012

Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.