

2010APAE
MATTE
GENERAL SIGNAGE

Grey Adhesive
with Air-Egress
Liner!

Digital Appetite

A GENERAL FORMULATIONS PUBLICATION

INTRODUCING

2 NEW Recipes For Success!

Great... Just got better!



classic 2010AP & 2030AP

2010AP & 2030AP with "AE"

Our classic 2010AP
and 2030AP
Matte and Gloss
White print
films NOW with
Air Egress (AE)
technology



Concepts newest flavor!



WARNING!

Side effects may include the following:

- Quicker installations.
- Unexpected free time.
- Increased productivity means better profit.
- 100% reduction in application fluid used. (dry apply only)



Available roll size: 54" x 150'

For more information contact your local Concept Dealer
or General Formulations on a Dealer near you.

Rolls 54"x 150'

NEW- 201-OAPAE with AIR EGRESS 90# liner- 319.00 (.47sq/ft.

NEW- 203-OAPAE with AIR EGRESS 90# liner- 319.00 (.47sq/ft.

Graphic Commerce Ltd.

Mississauga, On

phone (905)624-3124 toll free 1-800-543-2796

email - info@graphiccommerce.com

web - www.graphiccommerce.com



Product Bulletin

Concept[®] 201-OAPAE FLEXIBLE MATTE WHITE PVC PERMANENT ADHESIVE

Concept[®] 201-OAPAE (Air Egress) is a 3.4-mil premium matte white flexible calendered vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 90#AE layflat liner. This film is designed to accept a variety of solvent-based, UV curable and latex inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 90#AE liner offers excellent product layflat in a variety of ambient conditions along with ease of application for large format graphics.

Applications	Concept [®] 201-OAPAE is designed for large format interior or exterior signage, decals, nameplates and point-of-purchase displays.	
Thickness	Film	3.4 mils.
	Adhesive	.8 to 1.0 mils.
	Liner	7.5 mils.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+40°F.
	Service temperature	-40°F to +180°F.
Expected Exposure	Up to 3 years unprinted under normal exposure conditions.	
Exterior	Up to 5 years unprinted under normal exposure conditions.	
Interior		
Adhesion	To stainless steel	40 oz/in.
Average bond	PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.	
	Typical values. Individual values may vary.	
	Test your application thoroughly.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good.	
Solvent Resistance	Good	
Storage Stability	6-month shelf life when stored at 70°F and 50% relative humidity.	
Product Codes	201OAPAE-54	(54" x 150' roll)
Recommendations	Completely evaporate ink solvents before application. Failure to do so may facilitate solvent penetration resulting in premature vinyl degradation.	



**Manufacturer of Pressure Sensitive Films,
Traffic Graffice Floor Advertising Films,
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.